

FISA TEHNICA

Antifoane interne 3M Ultrafit

Antifoane interne reutilizabile tip bradut cu snur - 3M ULTRAFIT

- realizate dintr-un polimer patentat, cu 3 membrane asigurand o protectie de 29dB SNR
- antifoane **moi, confortabile, reutilizabile, lavabile**
- dopuri de urechi pentru zgomot, rezistente la umezeala

Antifoanele intene 3M Ultrafit sunt disponibile **impreuna cu o cutiuta pentru pastrarea in mod igienic dupa utilizare.**

Standard de conformitate:

SR EN 352-2: Protectori individuali împotriva zgomotului. Cerințe generale. Partea 2: Antifoane interne



© MONDO-ROMANIA.RO

Valori de atenuare

	Frequency (Hz) <i>f</i>								H	M	L	SNR
	63	125	250	500	1000	2000	4000	8000				
Mf (dB)	26.8	27.0	26.3	27.7	28.7	32.0	37.8	41.1	32.4	28.9	27.3	31.5
Sf (dB)	3.7	4.9	4.2	4.5	4.4	3.7	4.5	4.4	2.7	3.5	3.6	3.0
APVf (dB)	23.1	22.1	22.1	23.2	24.3	28.3	33.3	36.7	30	35	24	29

Key

f = Test frequency

Mf = Mean attenuation value

Sf = Standard deviation

APVf (Mf - Sf) = Assumed Protection Value

H = High-frequency attenuation value

M = Medium-frequency attenuation value

L = Low-frequency attenuation value

SNR = Single Number Rating (the value that is subtracted from the measured C-weighted sound pressure level, LC in order to estimate the effective A-weighted sound pressure level inside the ear)